

P-PS800 8-port 10 /100M PoE Switch

Key Features

- No need for setting and comply with IEEE 802.3at/af PoE standard
- Remote PoE PD Detection
- 11" Metal Case
- Holders to 19" Cabinet for Rack Mounted (optional)
- Auto-MDI/MDI-X, Auto-Negotiation
- Non-Blocking
- Internal Power Supply



Specifications	
<p>Standard</p> <ul style="list-style-type: none"> • IEEE 802.3 10BaseT • IEEE 802.3u 100BaseTX • IEEE 802.3x Full-duplex and Flow Control • IEEE 802.3at/af Power over Ethernet 	<p>Mechanical:</p> <ul style="list-style-type: none"> • LED Indicator <ul style="list-style-type: none"> ■ Per Port: Link / Act, PoE ■ PoE Port: Act/ Status ■ Per Unit: Power • Power Consumption <ul style="list-style-type: none"> ■ 120 Watts • Power Supply <ul style="list-style-type: none"> ■ 100~240V/AC, 50~60Hz • Power Output <ul style="list-style-type: none"> ■ 56V/DC per Port Output – 30 W Max per Port • Product Dimensions / Weight <ul style="list-style-type: none"> ■ 280 x 185 x 44 mm (L x W x H)/ 1.6kg
<p>Environmental Specification:</p> <ul style="list-style-type: none"> • Operating Temperature <ul style="list-style-type: none"> ■ 0 to 55 °C • Storage Temperature <ul style="list-style-type: none"> ■ -20 to 90 °C • Humidity <ul style="list-style-type: none"> ■ 10 to 90% RH (non-condensing) 	
<p>Number of Port</p> <ul style="list-style-type: none"> • 8-port 10/100BaseT(X) with PoE (Half/ Full power) • Total 120Watt 	<p>Box Dimension</p> <ul style="list-style-type: none"> • 295 x 240 x 65 mm (L x W x H)
<p>Performance:</p> <ul style="list-style-type: none"> • MAC Address: 4K • Buffer Memory: 64KB • Transmission Method: Store and Forward 	<p>Accessory</p> <ul style="list-style-type: none"> • Power Cord • User Manual • Rack-mount Holders
<p>Carton Dimension</p> <ul style="list-style-type: none"> • 440 x 400 x 270 mm ; 5 pcs/per carton 	<p>N.W / G.W</p> <ul style="list-style-type: none"> • 11 kg / 12 kg

Certification

FCC, CE, LVD